

SIDEWINDER HELMET MOUNT

MARKET

APPLICATIONS: Military, Marine, Aviation, Law Enforcement, Hardware/Tool, Automotive, Sporting Goods and Consumer.

DESCRIPTION:

Durable, compact quick release mount accepts all Sidewinder series flashlights. Patented compound action design allows for one handed installation, removal and operation of light on mount without the risk of inadvertent release. Stainless steel clamp design provides easy attachment to a variety of helmets, including PASGT, ACH and MICH style helmets, without damaging the helmet. Full 360 degree rotation with 16 detent locations provides fully adjustable targeting of illumination source onto task. Low profile internal wave form spring provides optimal position retention. Weighs less than 1 ounce.

CASE MATERIAL:

High impact super tough glass re-enforced nylon case. All hardware, fasteners and stampings are stainless steel. Exceptional durability and weather resistance. Available in Coyote and OD Green.

DIMENSIONS:

Width: 1.7 in. (4.3 cm) Height: 1.6 in. (4.1 cm) Depth: 1.0 in. (2.5 cm)
Protrusion from helmet surface (when mounted): <.53 in. (<1.35 cm)

WEIGHT:

0.93 ounces (26 grams)

FEATURES:

- Easy semi-permanent attachment to a variety of helmets without special tools. Clamping design does not damage helmet.
- Quick attachment/release of all Sidewinder series lights.
- Compound action design provides one handed installation and removal of lighting source without buttons or levers. Light is secured without risk of impact loss.
- Weighs less than 1 oz and protrudes less than .53 inches when attached.
- Full 360 degree rotation of lighting source.
- 16 detent locations for accurate placement of lighting source.

APPROVALS:

Meets applicable European Community Directives. 

WARRANTY:

Streamlight warrants its Sidewinder Helmet Mount will be free from manufacturing defects under normal use for 12 months after purchase. During the warranty period, at its sole discretion, Streamlight will repair or replace any defective part or product.

OPTIONAL**ACCESSORIES:**

N/A